



SHOWTEX BELGIË NV
Everaertsstraat 69
2060 ANTWERPEN

your delivery of
2009-09-29

your reference

our reference
PVH/9126

date
Zwijnaarde, 2009-10-13

Analysis Report 70885

Required tests :

Fabrics for curtains, drapes and window blinds – Flammability requirements

Identification number	Information given by the client	Date of receipt
T909776	X-foil	2009-10-06

Pros Van Hoeyland
order responsible

For further information, please contact our sectorial adviser Pros Van Hoeyland

This report runs to 2 pages and may be reproduced, as long as it is presented in its entire form, without written permission of Centexbel. The results of the analysis cover the received samples. Centexbel is not responsible for the representativeness of the samples.

ISO 17025



VAT BE 0459.218.289
CENTEXBEL-GENT
Technologiepark 7
BE-9052 Zwijnaarde
Tel. + 32 9 220 41 51 • Fax + 32 9 220 49 55
e-mail gent@centexbel.be

Fin. Acc. 210-0472965-45

IBAN BE44 2100 4729 6545

CENTEXBEL-BRUSSELS
Montoyerstraat 24 B2
BE-1000 Brussels
Tel. + 32 2 287 08 30 • Fax + 32 2 230 68 15

www.centexbel.be



Reference : T909776 - X-foil

Fabrics for curtains, drapes and window blinds – Flammability requirements

1. Method:

Test Method	- EN ISO 15025:2002
Standard	- BS 5867-2:2008
Pretreatment	- /
Deviations from the standard	- /

2. Test results:

End of tests: 13 October 2009

	length			width		
	1	2	3	1	2	3
flame or hole on edge	no	no	no	no	no	no
flaming debris droplets	no	no	no	no	no	no

Type B performance requirements

No part of any hole nor any part of the lowest boundary of any flame shall reach the top edge or either vertical edge.

There shall be no separation of any flaming debris droplets.

Conclusion : Flammability complies with the requirements of BS 5867-2:2008, type “B”